

Therma-Hygrometer

ideal for the home, office or factory

- max/min temperature & humidity function
- integral %rh & temperature

This therma-hygrometer simultaneously displays both the humidity and temperature in addition to indicating and recording the maximum and minimum temperature and humidity readings.

The hygrometer measures both humidity and temperature over the range of 0 to 50 °C and 10 to 99 %rh utilising the internal sensors.

This therma-hygrometer is ideal for monitoring both temperature and humidity in rooms, offices, factories and similar to ensure optimum working conditions are maintained.

The unit is housed in an ABS case, measuring 20 x 100 x 110 mm, that incorporates a useful foldaway stand and a keyhole slot for hanging on a wall.

order code	description
810-145	therma-hygrometer



specification	temperature	humidity
range	0 to 50 °C	10 to 99 %rh
resolution	0.1 °C/F	1 %rh
accuracy	±1 °C	±5 %rh
battery	1.5 volt AAA	
battery life	10000 hours	
display	dual custom LCD	
dimensions	20 x 100 x 110 mm	
weight	135 grams	

Therma-Hygrometer for panel-mounting

- displays both temperature & humidity
- easy panel-mounting installation

This panel-mounted therma-hygrometer simultaneously displays both humidity over the range of 20 to 99 %rh and temperature over the range of 0 to 49.9 °C with a resolution of 1 %rh and 0.1 °C. This instrument is ideal for OEMs for installing into equipment, i.e. vivariums, egg hatcheries and similar.

The therma-hygrometer is easily installed into a panel via a mounting hole with a minimum Ø33 mm cut-out. The unit incorporates a screw clamp with a maximum panel thickness of 7 mm.

The therma-hygrometer features a max/min memory function for both temperature and humidity. The unit is powered by a CR2032 coin cell battery with a life expectancy of 5000 hours continuous use.

order code	description
810-180	therma-hygrometer - panel



specification	temperature	humidity
range	0 to 49.9 °C	20 to 99 %rh
resolution	0.1 °C	1 %rh
accuracy	±1 °C	±5 %rh
sensor type	theristor	capacitance
battery	3 volt CR2032 lithium coin cell	
battery life	5000 hours	
display	dual custom LCD	
dimensions	Ø50 x 41 mm	
weight	42 grams	